



Application Alley

PARTNER | SOLVE | DELIVER

PCB Testing - Reed Relays

Reed Relays Are a Key Component in Testing Functional PCBs



Custom
Engineered
Solutions for
Tomorrow

Introduction

Functional PCB testers test printed circuit boards as large as 600 mm by 600 mm (or 2 foot square). These boards are in some cases, up to 20 layers thick, requiring 1000s of test points for functional verification. Each one of these test points may require as many as 6 switches each to provide the various voltages and currents for proper measurement. Because of size restrictions, isolation, relatively fast acting and good RF characteristics, reed relays are often chosen as the testing switch. A fully loaded tester can therefore, house over 20,000 reed relays. If there is one relay failure, this is equivalent to a failure level of 50 part per million (PPM). So the quality and reliability must reign supreme. Standex-Meder's reed relays have stepped up to meet these requirements; and their relays have become an accepted standard in the Automatic Test Equipment (ATE) industry.

Dimensions (mm)




Figure 1. CRR/CRF physical layout

Reed Relays are a Key Component in ATE Testers Testing Functional PCBs

Almost every piece of electronic equipment today uses printed circuit boards (PCBs). These PCBs range from a few square mm (0.08 square inches) to as large as 600 mm by 600 mm (2 ft by 2 ft). These PCBs can have only a few components to as many as thousands of components. On the larger PCBs there may be

1000s of test points that need their functionality determined. These usually work in conjunction with a bed of nails tester. This allows for the direct hook up to all the test points. Each one of these test points will need up to 6 switches to correctly switch in different voltages, currents and determine functionality. Semiconductor switches offer too much leakage, lack isolation and can interact with the actual test being undertaken. Electromechanical relays become unreliable after 1 million cycles. Reed relays make the best choice. Standex-Meder offers several reed relay series that represent a technically savvy low cost solution.




Figure 2. Reed relay signals pass/fail test results on functional PCB test.

Features

- High quality and reliability
- Very small size
- Ability to switch up to 1 amp

- Insulation resistance > 1012 Ohms
- Capable of switching and carrying up to 2 GHz
- Dielectric strength across the contacts 200 volts
- Low offset voltage < 1µV
- Contacts dynamically tested
- Low stable contact resistance
- Long life with up to a billion reliable operations
- Low stable contact resistance
- Long life with up to a billion reliable operations at relatively low levels

sizes of printed circuit boards.

Standex-Meder offers both standard through hole and surface mount in very small packages. All relays come with magnetic shielding allowing for very close packaging. Our surface mount CRR series can switch and carry DC to 2 GHz signals for use in high frequency requirements or fast digital pulses. Our standard SIL and MS in-line pin layouts are both considered standards in the industry and meet the stringent conditions for high quality and reliability. All series can carry up to 1 amp and hold off 200 Volts across the contacts.

Specifications (@ 20°C) CRR Series



	Min	Typ	Max	Units
Coil characteristics				
Coil resistance	135	150	165	Ω
Coil voltage		5.0		V
Pull-In			3.75	V
Drop-Out	0.85			V
Switch characteristics				
Contact rating			10	Watts
Switching voltage			170	V
Switching current			0.5	Amps
Carry current			0.5	Amps
Static contact resistance			250	mΩ
Dynamic contact resistance			250	mΩ
Dielectric from voltage across the contacts	210			V
Dielectric from voltage coil to contacts	1000			V
Operate time			0.1	msec
Release time			20	µsec
Operate temp	-20		100	°C
Storage temp	-55		125	°C

*Coil parameters will vary by 0.2% /oC

Applications

- Ideal for use in testers and Automatic Test Equipment that test the functionality of all



Surface Mount Reed Relay Series

Series	Dimensions			Illustration
		mm	inches	
SRR	W	4.0	0.157	
	H	3.2	0.126	
	L	7.5	0.295	
CRR	W	4.4	0.173	
	H	3.5	0.137	
	L	8.6	0.338	

Standex-Meder's reed relays use hermetically sealed reed switches that are further packaged in strong high strength thermoset molding compound, and can therefore be subject to various environments without any loss of reliability.

The reed relay is an excellent choice because it can operate reliably over a wide temperature range, and represents an economical way to carry out billions of switching operations.

Through Hole Reed Relay Series

Series	Dimensions			Illustration
		mm	inches	
MS	W	3.8	0.150	
	H	6.8	0.268	
	L	15.2	0.598	
SIL	W	5.08	0.200	
	H	7.8	0.307	
	L	19.08	0.780	

Find out more about our ability to propel your business with our products by visiting www.standexmeder.com or by giving us a hello@standexelectronics.com today! One of our brilliant engineers or solution selling sales leaders will listen to you immediately.

About Standex-Meder Electronics

Standex-Meder Electronics is a worldwide market leader in the design, development and manufacture of standard and custom electro-magnetic components, including magnetics products and reed switch-based solutions.

Our magnetic offerings include planar, Rogowski, current, and low- and high-frequency transformers and inductors. Our reed switch-based solutions include Meder, Standex and OKI brand reed switches, as well as a complete portfolio of reed relays, and a comprehensive array of fluid level, proximity, motion, water flow, HVAC condensate, hydraulic pressure differential, capacitive, conductive and inductive sensors.

We offer engineered product solutions for a broad spectrum of product applications in the automotive, medical, test and measurement, military and aerospace, as well as appliance and general industrial markets.

Standex-Meder Electronics has a commitment to absolute customer satisfaction and customer-driven innovation, with a global organization that offers sales support, engineering capabilities, and technical resources worldwide.

Headquartered in Cincinnati, Ohio, USA, Standex-Meder Electronics has eight manufacturing facilities in six countries, located in the United States, Germany, China, Mexico, the United Kingdom, and Canada.

For more information on Standex-Meder Electronics, please visit us on the web at www.standexmeder.com.

Contact Information:

Standex-Meder Electronics
World Headquarters
4538 Camberwell Road
Cincinnati, OH 45209 USA

Standex Americas (OH)
+1.866.STANDEX (+1.866.782.6339)
info@standexelectronics.com

Meder Americas (MA)
+1.800.870.5385
salesusa@standexmeder.com

Standex-Meder Asia (Shanghai)
+86.21.37820625
salesasia@standexmeder.com

Standex-Meder Europe (Germany)
+49.7731.8399.0
info@standexmeder.com