

Dimensions mm[inch]
tolerances acc. to DIN ISO 2768-m
 Toleranzen gem. DIN ISO 2768-m

Isometric
Scale 2:1
 Maßstab 2:1

Marking
according to EN60062/factory code
 gem. EN60062/Fertigungsstätte

MEDER electronic
SIL15-1A72-71D
YW/P

Layout
Top view
 Draufsicht

| Coil Data at 20 °C | Conditions | Min | Typ | Max | Unit |
|--------------------|--|-------|-------|-------|------|
| Coil resistance | | 1.800 | 2.000 | 2.200 | Ohm |
| Coil voltage | | | 15 | | VDC |
| Rated power | | | 113 | | mW |
| Coil current | | | 7,5 | | mA |
| Thermal resistance | max. Relay temperature = operating temperature + self heating | | 110 | | K/W |
| Inductance | | | 250 | | mH |
| Pull-In voltage | | | | 10,5 | VDC |
| Drop-Out voltage | | 2,2 | | | VDC |

| Contact data 66/3 | Conditions | Min | Typ | Max | Unit |
|-----------------------------|--|-----|-----|-----|------|
| Contact rating | Any DC combination of V & A not to exceed their individual max.'s | | | 10 | W |
| Switching voltage | DC or Peak AC | | | 200 | V |
| Switching current | DC or Peak AC | | | 0,5 | A |
| Carry current | DC or Peak AC | | | 1 | A |
| Contact resistance static | Measured with 40% overdrive Start Value | | | 150 | mOhm |
| Insulation resistance | RH <45 %, 100 V test voltage | 10 | | | TOhm |
| Breakdown voltage (< 20 AT) | according to EN 60255-5 | 250 | | | VDC |
| Operate time incl. bounce | measured with 40% overdrive | | | 0,5 | ms |
| Release time | measured with no coil excitation | | | 0,1 | ms |
| Capacity | @ 10 kHz across open switch | | 0,2 | | pF |

| Special Product Data | Conditions | Min | Typ | Max | Unit |
|------------------------------------|------------------------------------|-----|---------------------------|-----|-------|
| Number of contacts | | | 1 | | |
| Contact - form | | | A - NO | | |
| Dielectric Strength Coil/Contact | according to EN 60255-5 | 1,5 | | | kV DC |
| Insulation resistance Coil/Contact | RH <45%, 200 VDC measuring voltage | 100 | | | GOhm |
| Capacity Coil/Contact | @ 10 kHz | | 0,7 | | pF |
| Case colour | | | black | | |
| Housing material | | | epoxy resin | | |
| Connection pins | | | CuFe2P, tin plated | | |
| Magnetic Shield | | | no | | |
| Approval | | | UL-File No. NRNT2.E156887 | | |
| Approval | | | UL-File No. NRNT8.E156887 | | |
| Reach / RoHS conformity | | | yes | | |

| Environmental data | Conditions | Min | Typ | Max | Unit |
|--------------------|------------|-----|-----|-----|------|
|--------------------|------------|-----|-----|-----|------|

Modifications in the sense of technical progress are reserved



Products for tomorrow...

Europe: +49 / 7731 8399 0 | Email: info@meder.com
USA: +1 / 508 295 0771 | Email: salesusa@meder.com
Asia: +852 / 2955 1682 | Email: salesasia@meder.com

Item No.:
3315172171
Item:
SIL15-1A72-71D

| Environmental data | Conditions | Min | Typ | Max | Unit |
|-----------------------|-----------------------------|-----|-----|-----|--------------|
| Shock | 1/2 sine wave duration 11ms | | | 50 | g |
| Vibration | from 10 - 2000 Hz | | | 20 | g |
| Operating temperature | | -20 | | 70 | °C |
| Storage temperature | | -35 | | 95 | °C |
| Soldering temperature | wave soldering max. 5 sec. | | | 260 | °C |
| Washability | | | | | fully sealed |

| General data | Conditions | Min | Typ | Max | Unit |
|--------------|------------|-----|-----|-----|----------------|
| Total weight | | | 1,5 | | g |
| Packaging | | | | | Stange 25 pcs. |

Modifications in the sense of technical progress are reserved

Designed at: 09.03.04 Designed by: SCHELLHORN
Last Change at: 14.09.12 Last Change by: NMIHAI

Approval at: 16.03.11 Approval by: KOLBRICH
Approval at: 19.09.12 Approval by: CRUF

Version: 05