


### Preliminary Datasheet

**Dimensions mm[inch]**  
 tolerances acc. to DIN ISO 2768-m  
 Toleranzen gem. DIN ISO 2768-m



**Isometric**  
 Scale 1:1  
 Maßstab 1:1



Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull-In excitation (Reference value)	Reed switch unmodified measured in coil- "define operation"	10		20	AT
Test-Coil	Reed switch unmodified	Standex coil (KMS-50)			

Contact data 08/6	Conditions	Min	Typ	Max	Unit
Contact - No.		08/6			
Contact-form		A			
Contact-material		PGM-alloy			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			50	W
Switching voltage	DC or Peak AC			200	V
Switching current	DC or Peak AC			1.5	A
Carry current	DC or Peak AC			2.5	A
Contact resistance static	Start value			100	mOhm
Insulation resistance	RH <45 %, 100 V test voltage	10			GOhm
Breakdown voltage	according to EN 60255-5	250			VDC
Operate time incl. bounce				0.8	ms
Release time	measured with no coil excitation			0.1	ms
Capacity	@ 10 kHz across open switch		0.3		pF

Special Product Data	Conditions	Min	Typ	Max	Unit
Reach II / RoHS conformity		yes			

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine, duration 11ms, in 3 axis			50	g
Vibration	from 10 - 2000 Hz			20	g
Ambient temperature		-40		125	°C
Storage temperature		-50		155	°C
Soldering temperature	wave soldering max. 5 sec.			260	°C

Modifications in the sense of technical progress are reserved

Designed at: 14/12/10    Designed by: AAI  
 Last Change at:            Last Change by:

Approval at:                    Approval by:  
 Approval at:                    Approval by:

Rev. No.: 01